SECTION 3: Specifications

NC-001 / NC-002 Product Specifications

Numbering Head	Heavy-duty rotary type
Type and Figure Size	Gothic 3/16" (4.7 mm) 7-digit
Maximum # Heads/Ring	Straight horizontal: - 4 heads per ring - Max. ring assemblies: 3 Convex vertical: - 4 heads per ring - Max. ring assemblies: 3
Numbering Margins	Left and right: 0" Top: 3/16" (4.7 mm) Bottom: 12.2" (310 mm) from lead edge
Minimum distance between numbers	Vertical forward: 1.75" (45 mm) Vertical backward: 2.35" (59 mm) Horizontal forward: 2.35" (59 mm) Horizontal backward: 1.75" (45 mm)
Signature Attachment	Area: 2"x1" (5 cm x 2.5 cm)
Print Speed	Same as Risograph 60 up to 130 ppm (3,600 to 7,800 prints/hour)
Safety	Driver declutching device Error diagnostic compliance with duplicator
Dimensions	Length: 20" (50 cm) Width: 10" (25 cm) Height: 11.5" (29 cm)
Weight	20.1 lbs. (9.07 kg)

Accessories and Equipment

Numbering Heads	Horizontal forward Horizontal backward Vertical forward Vertical backward
Imprinting	Designation block for polymer plate
Miscellaneous	Additional ring and cam Repeat wheels #2 to #6 Skip wheel Red Inked Rollers Black Inked Rollers

For part numbers, please refer to the NC Parts Manual.

(Specifications subject to change without notice.)